



Vērtņes rāmis:

3D stiepļu panelis (50 x 200 mm, d - 4 mm),
rāmis sametināts no 40x40 mm caurulēm
Rāmja augstums ir vienāds ar žoga augstumu

Stabi:

60 x 60 mm caurules ar plastmasas uzgali augšpusē.

Vārtu komplektā iekļautas:

LOCINOX eņģes G90Z-M20, nodrošina iespēju atvērt 90 grādu leņķi
LOCINOX plastmasas slēdzene LAKZ P1 un plastmasas atduris SMKL QF

Izvēles piederumi:

LOCINOX metāla slēdzene LAKQ U2 un metāla atduris SAKL QF

Pieejamā apdare:

Karsti cinkots pārklājums, kas atbilst EN1461
Gruntēti un pulverkrāsoti jebkurā RAL tonī



LOCINOX plastmasas slēdzene LAKZ P1
Ekonomiskiem staigāšanas vārtiem, poliamīda
korpusā ar nerūsošā tērauda mehānismu.
Šī slēdzene iesakāma kā standarts visiem neliela
izmēra vārtiem. 25 cm gara masīva nerūsošā
tērauda mēlīte garantē drošu vārtu aizslēgšanu



LOCINOX metāla slēdzene LAKQ U2
Rūpniecībā izmantojama slēdzene ar alumīnija
korpusu un nerūsošā tērauda mehānismu. Mēs
iesakām šo slēdzeni kā standartu visiem rūpniecībā
izmantojamiem vārtiem. 20 mm garš pielāgojamās
bultskrūves ļauj lieliski pielāgot slēdzenes
mehānismu. 25 cm gara masīva nerūsošā tērauda
mēlīte garantē drošu vārtu aizslēgšanu.



LOCINOX eņģes G90Z-M20
Karsti cinkotas 90° eņģes. 27 mm garas,
regulējamas. Perfekts risinājums nelieliem
rūpniecībā izmantojamiem



LOCINOX plastmasas atduris SMKL QF
Poliamīda atduris staigājamiem un dārza vārtiem.
Ātras fiksēšanas mehānisms nodrošina ātru un
stingru uzstādīšanu uz četrstūrīgiem stabiem.
40 mm vārtu profilēm.



LOCINOX plastmasas atduris SMKL QF
Alumīnija atduris, tiek izmantots kā standarts
visiem staigājamiem, dārza, dekoratīviem un
rūpniecībā izmantojamiem vārtiem.

Izmēri

Atveramais platums	Augstums (mm)								
800 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
1000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
1200 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430



Leaf Frame:

3D wire panel (50x200 mm, d-4 mm),
welded from tubes 40x40 (mm)
Frame height = Fence height

Posts:

Tubes 60x60 mm, with plastic cap on the top.

Gates include:

LOCINOX hinges G90Z-M20 allows to open 90 degrees
LOCINOX plastic lock LAKZ P1 and plastic keep SMKL QF

Optional accessories:

LOCINOX metal lock LAKQ U2 and metal keep SAKL QF

Available finishes:

Hot Dipped Galvanised according to EN1461
Primed and powder coated in RAL colour



LOCINOX plastic lock LAKZ P1
Economical walking gate with polyamide housing and stainless steel mechanism. This lock is advised as a standard for all small gates. A massive stainless steel throw of 25 mm guarantees a secure locking.



LOCINOX metal lock LAKQ U2
Industrial lock with aluminium housing and stainless steel mechanism. We advise this lock as a standard for all your industrial gates. The 20 mm continuous adjustability of the bolts allows a perfect alignment of your locking mechanism. A massive stainless steel throw of 25 mm guarantees a secure locking.



LOCINOX hinges G90Z-M20
Hot-dip galvanised 90° hinge. 27 mm adjustable
The perfect solution for all your small industrial gates.



LOCINOX plastic keep SMKL QF
Polyamide keep for walk- and garden gates.
The Quick-fix fixing ensures a fast and strong mounting on square posts. For gate-profiles 40mm.



LOCINOX plastic keep SMKL QF
Aluminium keep used as a standard for all your walk-, garden-, ornamental and industrial gates.
The unique Quick-fix fixing ensures a fast and strong mounting. The adjustable stopplate with rubber accepts different gate profiles till 60mm.

SIZES

Clear opening width	Height (mm)									
800 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430	
1000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430	
1200 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430	