

## CARGO EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL

Use

Designed for building, renovation and heavy duties. Loading capacity 200 kg.



Product advantages

- Excellent balance and weight distribution with 70% of the load positioned over the wheel. Its
  design allows an optimal use and reduces risk of injury and strains for the user.
- · Bi-material handgrips for added comfort.
- This tray has a squared bottom and a trapezoid upper edge to enable the load of squared elements (parpaings, bricks...) and the displacement of liquid loads on the wheel.
- Equipped with a pneumatic wheel to enhance comfort.

## Technical data

## CARGO EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL (4051 DG)

Tray	Galvanized 100 I, 1 mm thickness, treated anti-corrosion.  Frontal and lateral ribs for additional strength.
Frame	Ø 32 mm black painted with integrated tipping bar and tray supports.
Wheel	Pneumatic Ø 400 mm, metal disc rim, long lasting notched tyre.  Maximum pressure: 2 bars.

Sizes	1400 x 670 x 580 mm.
Weight	13,7 kg.
Spare parts	Wheel PF 154 Code: 309016701 EAN: 315503090167 8 Galvanized tray 100 I. Code: 309007101 EAN: 315503090071 8
Codes	Unassembled x 10 : 301141610 EAN : 315503011416 0 Delivered by TC 40' dry : 1500 units



