

CARGO EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL

Use

Designed for building, renovation and heavy duties. Loading capacity 200 kg.



Product advantages

- Painted frame, with galvanized feet and a new feet support : one piece galvanized feet support, for more rigidity.
- Excellent balance and weight distribution with 70% of the load positioned over the wheel. Its design allows an optimal use and reduces risk of injury and strains for the user.
- · Bi-material handgrips for added comfort.
- This tray has a squared bottom and a trapezoid upper edge to enable the load of squared elements (parpaings, bricks...) and the displacement of liquid loads on the wheel.
- Equipped with a pneumatic wheel to enhance comfort.

Technical data

CARGO EXCELLIUM 100 GALVANIZED TRAY PNEUMATIC WHEEL (4051 DG)





Tray	Galvanized 100 I, 1 mm thickness, treated anti-corrosion. Frontal and lateral ribs for additional strength.
Frame	Ø 32 mm black painted with integrated tipping bar, tray supports and a new galvanized feet support.
Wheel	Pneumatic Ø 400 mm, with ball bearings, metal disc rim, long lasting notched tyre. Maximum pressure: 2 bars.

Sizes	1400 x 670 x 580 mm.
Weight	13,7 kg.
Spare parts	Wheel PF 118 Code: 309032801 EAN: 315503090328 3 Galvanized tray 100 I. Code: 309007101 EAN: 315503090071 8
Codes	Unassembled x 10 : 301141710 EAN : 315503011417 7 Delivered by TC 40' dry : 1500 units



welcome@haemmerlin.com - www.haemmerlin.com

